

2G11 LEDs

CL-2G11 Series



Description

Inno LED's Replacements for 2G11 CFLs are the best and economical solution for upgrading to an energy saving and maintenance free lighting solution with your existing luminaires. Aesthetically similar to 2G11 CFL tubes and fits in existing holder without disturbing your fitting, works only without choke.

Features:

- physically similar
- upto 50% power saving vs 2G11 CFL
- remove choke and fit in existing luminaire
- frosted cover- glare free illumination
- ribbed heatsink
- colors - cool white

Highlights:

- everlight LED 120 Lm/W
- metal PCB
- full bridge driver
- extruded aluminium heatsink

| Specifications | | | |
|-----------------------|---------------------------------|---------------|---------------|
| Models | CL-2G11-W-12W | CL-2G11-W-18W | CL-2G11-W-22W |
| Length | 2' - 2G11 CFL eqv. | | |
| Power Consumption | 12W | 18W | 22W |
| Lumens | >1150 | >1730 | >2110 |
| Operating Voltage | 210 ~ 270 VAC, 50 Hz; eff. >80% | | |
| Power Factor | ≥ 0.95 | | |
| Color Temperature | 6500 ~ 6700 K (CRI - >80%) | | |
| Beam Angle (typical) | > 110° | | |
| Lifetime (typical) | 50,000 hours | | |
| Operating Temperature | -20°C to 60°C | | |
| Holder Type | 4 pin 2G11 holder plug | | |