

# COB STREET LIGHTS



## IL-DY Series



## Description

Inno LED's COB Street Lights come with a dashing Aerodynamic look that enriches the aesthetics of your street. Superfine die casting for effective heat dissipation offers longevity and its double convex elliptical lenses offer a wider beam angle stretching the spacing between the mounting columns. The ideal choice for hotel and office street lighting. Save energy in style with COB LED Street lights.

**Features:**

- futuristic leaf design
- customizable in grey (standard)/ white/ black/ red/ green colors
- ribbed design for better heat dissipation
- double convex lens for wide coverage


**Highlights:**

- cree LED 140 Lm/W
- fullham driver
- IP66
- powder coated pressure die-cast aluminium

## Specifications

Models	IL-DY-C-30W	IL-DY-C-50W	IL-DY-C-100W
Power Consumption	30W	50W	100W
Lumens	>3600	>6000	>12000
Operating Voltage	150 ~ 270 VAC, 50 Hz; eff. >80%		
Power Factor	≥ 0.98		
Color Temperature	6500 ~ 6700 K (CRI - >80%)		
Beam Angle (typical)	> 100°		
Lifetime (typical)	40,000 hours		
Operating Temperature	-20°C to 60°C		
Enclosure	IP65, Pressure Die- cast Aluminium Enclosure, glass lens		
Size/ Mounting dia. (mm)	400*170*80/ max. Ø50	500*210*85/ max. Ø60	700*270*120/ max. Ø80

# Dimension Diagram



All dimensions are in mm

Model	A	B	C	D
IL-DY-C-30W	400	170	50	80
IL-DY-C-50W	500	120	60	85
IL-DY-C-100W	700	270	80	120