

SURFACE SQUARE LIGHTS



CL-SS Series



Description

Inno LED's Surface Downlights are ideal for applications that require a green general lighting solutions for instance in parking lot/ general lobby of offices and commercial spaces. Use of simple design and sturdy material and heatsink ensure a long life and hassle free maintenance experience. Their extremely low power consumption results in significant energy savings of upto 40% compared with traditional CFL downlights.

Features:

- elegant looks
- upto 40% power saving vs CFL downlights
- frosted diffuser- glare free illumination
- square surface downlights
- colors - cool white

Highlights:

- everlight LED 120 Lm/W
- built-in driver
- PC diffuser
- powder coated MS heatsink

Specifications

Models	CL-SS-W-15W	CL-SS-W-22W	CL-S11-W-25W	CL-S22-W-40W
Power Consumption	15W	22W	25W	40W
Lumens	>1400	>2000	>2300	>3750
Operating Voltage	210 ~ 270 VAC, 50 Hz; eff. >80%			
Power Factor	≥ 0.95			
Color Temperature	6500 ~ 6700 K (CRI - >80%)			
Beam Angle (typical)	120°			
Lifetime (typical)	40,000 hours			
Operating Temperature	-20°C to 60°C			
Enclosure	Powder Coated MS, PC Diffuser			
Size (mm)	165*35*165	220*35*220	295*55*295	590*55*590