

# Industrial Signal Converter

Serial (RS-232) to USB

# XV-USB232



## SALIENT FEATURES

- ◆ Compact
- ◆ LED Indication
- ◆ Built in Clock Ckt.

## Ratings and Specifications

Model	XV-USB232
Type	RS- 232 to USB (2 Way)
Indication	LED for TX, Rx active
Baud Rate	Auto Select - 300 to 1Mbps
Parity	Support for Odd/ Even/ Mark/ Space/ None
Power Supply	5 VDC (self powered from USB)
Shock Resistance	10 G- X,Y, Z three directions
Ambient Temperature	Operation: -25° ~ 50°C; Storage: -30° ~ 60°C (non- freezing; non- condensing)
Ambient Humidity	Operation: 35 ~ 85% RH; Storage: 35 ~ 90% RH (non- condensing)
Protection Class	IP51
Weight	aprox. 26g (excluding cable)
Dimensions	52 x 43 x 22 mm (excluding cable)
Material	ABS

Cat. No. XV-USB232-C12

Exclusively Represented by:

Intech Systems Chennai Pvt Ltd  
 S-2, Guindy Industrial Estate  
 Chennai - 600 032. Ph: 4353 8888  
 Email: [info@intechchennai.com](mailto:info@intechchennai.com)

  
[www.inno.sg](http://www.inno.sg)

© INNO, Rights Reserved  
 In the interest of continuous product improvement  
 specifications are subject to change without notice